

### DIRECTIONS

404 can be mixed on either a weight or volume basis when using less than full kit contents at one time. Kit contents are pre-weighted so full contents of A and B can be combined completely for best mixing. If using less than full contents, mix as follows: By weight- Mix 2.5 parts A to 1 part B. By Volume: Mix 4 parts A to 1 part B. See TDS for detailed instructions.



### CAUTION

PLEASE REFER TO THE MSDS SHEETS FOR MORE DETAILED PRECAUTIONARY MEASURES, HANDLING INSTRUCTIONS AND EMERGENCY PROCEDURES

### FIRST-AID

EYES - flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation - get medical attention. SKIN - flush with water and then wash with soap and water, launder contaminated clothing before reuse - get medical attention if irritation persists. INHALATION - remove to fresh air and assist breathing as necessary-get medical attention. INGESTION- If appreciable amounts have been swallowed-get medical attention

404 is an epoxy based patching system for repairs and reinforcement of concrete, brick, metal, and wood vertical and inverted surfaces which will not sag or slide. Coverage is 7-8 sq. ft. at 1/4 inch per kit.

Part A		Health	2
		Fire	1
		Reactivity	0
		Personal Protection	
Part B		Health	3
		Fire	1
		Reactivity	0
		Personal Protection	

